

**Product Type Product Sizes Material of Construction** Body&Cap **Sealing O-Ring Sight Glass Impeller/Rotor Connection Way** 

## Max. Operating Pressure **Compatible Medium**

## **Brass Flow Indicator**

:SG-YL11-05 :DN15 to DN50(1/2"Inch to 2"Inch)

:SS304 / SS316 / SS316L or Brass :PTFE(White)/NBR(Black)/Viton(Black) :Tempered Glass/Quartz Glass :Plastic(Red)/PTFE(Red) :NPT,BSPP,BSPT Female Thread Max. Working Temperature :100°C / 212°F for Plastic Impeller&NBR or NBR O-Ring 200°C / 392°F for PTFE Impeller&O-Ring :0.6MPa / 6Bar / 87PSI(Up to 1.6MPa Customization) :Water / Oil / Gas / Air / Liquids



## Wenzhou Luosimeng Machinery Co., Ltd. (Sight Flow Indicator Manufacturer)

Tel.:+86-577-86896383

Fax:+86-577-86998170

Email:sales@rosemoun.com.cn sales1@rosemoun.com.cn rosemounmachinery@hotmail.com Web:www.rosemoun.com

Mobile:+86-13091902237 Factory:102nd&201st Room,19th Building,No. 696,5th Binhai Road,Economic and Technological Developme Zone Wenzhou, Zhejiang P.R.China