

Slow Flow Sight Flow Indicator

Product Type	:SG-YL11-05
Product Sizes	:DN6 to DN10(1/8" Inch to 3/8" Inch)
Material of Construction	
Body&Cap	:SS304 / SS316 / SS316L or Brass
Sealing O-Ring	:PTFE(White)/NBR(Black)/Viton(Black)
Sight Glass	:Tempered Glass/Quartz Glass
Impeller/Rotor	:Plastic(Red)/PTFE(Red)
Connection Way	:NPT,BSPP,BSPT Female Thread
Max. Working Temperature	:100°C / 212°F for Plastic Impeller&NBR or NBR O-Ring 200°C / 392°F for PTFE Impeller&Gasket
Max. Operating Pressure	:0.6MPa / 6Bar / 87PSI(Up to 1.6MPa Customization)
Compatible Medium	:Water / Oil / Gas / Air / Liquids

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

Wenzhou Luosimeng Machinery Co.,Ltd.
(Sight Flow Indicator Manufacturer)