

Flow Indicator Price

Product Type	:SG-YL11-20
Product Sizes	:DN6 to DN25(1/8”Inch to 1”Inch)
Material of Construction	
Body&Cap&Pole	:SS304 / SS316 / SS316L or Carbon Steel(WCB)
Sealing Gasket	:PTFE(White)/NBR(Black)/Viton(Black)
Sight Glass	:Tempered/Borosilicate/Quartz/Aluminosilicate Glass
Impeller/Rotor	:Plastic (Red) or PTFE (Red or Blue)
Connection Way	:NPT,BSPP,BSPT Female Thread
Max. Working Temperature	:100°C / 212°F for Plastic Impeller&NBR or Viton Gasket 200°C / 392°F for PTFE Impeller&Gasket
Max. Operating Pressure	:1.6MPa / 16Bar / 232PSI (Up to 5.0MPa Customization)
Compatible Medium	:Water / Oil / Gas / Air / Liquids



G 1/4	L:90mm	A:35mm	B:53mm	C:11mm	D:47mm	E:8mm	F:62mm	0.63Kg
G 3/8	L:90mm	A:35mm	B:53mm	C:15mm	D:47mm	E:8mm	F:62mm	0.61Kg
G 1/2	L:90mm	A:35mm	B:53mm	C:19mm	D:47mm	E:8mm	F:62mm	0.59Kg
G 3/4	L:94mm	A:35mm	B:53mm	C:24mm	D:47mm	E:8mm	F:62mm	0.62Kg
G 1	L:100mm	A:35mm	B:53mm	C:30mm	D:47mm	E:8mm	F:62mm	0.67Kg
G 1 1/4	L:110mm	A:44mm	B:66mm	C:39mm	D:56mm	E:8mm	F:77mm	1.17Kg
G 1 1/2	L:124mm	A:50mm	B:70mm	C:45mm	D:60mm	E:8mm	F:92mm	1.42Kg
G 2	L:160mm	A:63mm	B:85mm	C:57mm	D:75mm	E:8mm	F:103mm	2.11Kg

Wenzhou Luosimeng Machinery Co.,Ltd. (Sight Flow Indicator Manufacturer)