

## Threaded Water Flow Indicator

|                                 |   |
|---------------------------------|---|
| <b>Product Type</b>             | :SG-YL11-55   |
| <b>Product Sizes</b>            | :DN6 to DN50(1/8”Inch to 2”Inch)  |
| <b>Material of Construction</b> |   |
| <b>Body&amp;Cap</b>             | :SS304 / SS316 / SS316L,Brass,Carbon Steel(WCB)   |
| <b>Sealing O-Ring</b>           | :PTFE(White)/NBR(Black)/Viton(Black)  |
| <b>Sight Glass</b>              | :Tempered Glass/Quartz Glass  |
| <b>Impeller/Rotor</b>           | :Plastic(Red)/PTFE(Red)   |
| <b>Connection Way</b>           | :NPT,BSPP,BSPT Male Thread  |
| <b>Max. Working Temperature</b> | :100°C / 212°F for Plastic Impeller&NBR or NBR O-Ring<br>200°C / 392°F for PTFE Impeller&O-Ring |
| <b>Max. Operating Pressure</b>  | :0.6MPa / 6Bar / 87PSI(Up to 1.6MPa Customization)  |
| <b>Compatible Medium</b>        | :Water / Oil / Gas / Air / Liquids  |



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

## Wenzhou Luosimeng Machinery Co.,Ltd. (Sight Flow Indicator Manufacturer)