

## Customized Water Flow Indicator

<b>Product Type</b>	:SG-YL61-20
<b>Product Sizes</b>	:DN15 to DN100(1/2”Inch to 4”Inch)
<b>Material of Construction</b>	
<b>Body&amp;Cap</b>	:SS304 / SS316 / SS316L or Carbon Steel(WCB)
<b>Sealing Gasket</b>	:PTFE(White)/NBR(Black)/Viton(Black)
<b>Sight Glass</b>	:Tempered/Borosilicate/Quartz/Aluminosilicate Glass
<b>Impeller/Rotor</b>	:Plastic (Red) or PTFE (Red or Blue)
<b>Connection Way</b>	:Butt Weld/Socket Weld
<b>Max. Working Temperature</b>	:100°C / 212°F for Plastic Impeller&NBR or Viton Gasket 200°C / 392°F for PTFE Impeller&Gasket
<b>Max. Operating Pressure</b>	:1.6MPa / 16Bar / 232PSI (Up to 5.0MPa Customization)
<b>Compatible Medium</b>	:Water / Oil / Gas / Air / Liquids

**LSMSFI**

Wenzhou Luosimeng Machinery Co.Ltd.

**LSMSFI**

Wenzhou Luosimeng Machinery Co.Ltd.

**LSMSFI**

Wenzhou Luosimeng Machinery Co.Ltd.

**Wenzhou Luosimeng Machinery Co.,Ltd.**  
(Sight Flow Indicator Manufacturer)