

Polished Sight Flow Indicator

Product Type	:SG-ZT11-30D
Product Sizes	:DN8 to DN50(1/4”Inch to 2”Inch)
Material of Construction	
Body&Cap	:SS304 / SS316 / SS316L or Carbon Steel(WCB)
Sealing Gasket	:PTFE(White)/NBR(Black)/Viton(Black)
Window	:Tempered/Borosilicate/Quartz/Aluminosilicate Glass
Connection Way	:NPT,BSPP,BSPT Female Thread
Max. Working Temperature	:100°C / 212°F for Plastic or NBR Gasket 200°C / 392°F for PTFE Gasket
Max. Operating Pressure	:1.6MPa / 16Bar / 232PSI (Up to 5.0MPa Customization)
Compatible Medium	:Water / Oil / Gas / Air / Liquids etc

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

Wenzhou Luosimeng Machinery Co.,Ltd.
(Sight Flow Indicator Manufacturer)