

## DIN Flange Water Flow Indicator

**Product Type** :SG-ZT41-202  
**Product Sizes** :DN15 to DN65(1/2”Inch to 2 1/2”Inch)  
**Material of Construction**  
**Body&Cap&Flap** :SS304 / SS316 / SS316L or Carbon Steel(WCB)  
**Sealing Gasket** :PTFE(White)/NBR(Black)/Viton(Black)/Graphite(Black)  
**Sight Glass** :Tempered/Borosilicate/Quartz/Aluminosilicate Glass  
**Connection Way** :ANSI 150LB/300LB,JIS 5K/10K,DIN,GB Flange  
**Max. Working Temperature** :100°C / 212°F for NBR or Viton Gasket  
200°C / 392°F for PTFE Gasket  
1000°C / 1832°F for Graphite Gasket  
**Max. Operating Pressure** :1.6MPa / 16Bar / 232PSI (Up to 5.0MPa Customization)  
**Compatible Medium** :Water / Oil / Gas / Air / Liquids



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

**Wenzhou Luosimeng Machinery Co.,Ltd.**  
(Sight Flow Indicator Manufacturer)

Tel.:+86-577-86896383    Fax:+86-577-86998170    Mobile:+86-13091902237    Factory:102nd&201st Room,19th Building,No. 696,5th Binhai Road,Economic and Technological Developme Zone Wenzhou,Zhejiang P.R.China

Web:www.rosemoun.com