

Double Window Sight Glass Flow Indicator

Product Type :SG-ZT41-205
Product Sizes :DN80 & DN100(3”Inch & 4”Inch)
Material of Construction
Body&Cap&Bolt&Flap :SS304 / SS316 / SS316L or Carbon Steel(WCB)
Sealing Gasket :PTFE(White)/NBR(Black)/Viton(Black)/Graphite(Black)
Sight Glass :Tempered/Borosilicate/Quartz/Aluminosilicate Glass
Connection Way :ANSI 150LB/300LB,JIS 5K/10K,DIN,GB Flange
Max. Working Temperature :100°C / 212°F for NBR or Viton Gasket
200°C / 392°F for PTFE Gasket
1000°C / 1832°F for Graphite Gasket
Max. Operating Pressure :1.6MPa / 16Bar / 232PSI (Up to 5.0MPa Customization)
Compatible Medium :Water / Oil / Gas / Air / Liquids



LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.



LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.



LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.



LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

Wenzhou Luosimeng Machinery Co.,Ltd. (Sight Flow Indicator Manufacturer)