

## PTFE Ball Flow Indicator

<b>Product Type</b>	:SG-FQ11-038
<b>Product Sizes</b>	:DN6 to DN25(1/8”Inch to 1”Inch)
<b>Material of Construction</b>	
<b>Body&amp;Cap</b>	:SS304 / SS316 / SS316L,Carbon Steel(WCB)
<b>Floating Balls</b>	:Plastic(Red/Blue)/PTFE(Red)
<b>Sealing O-Ring</b>	:PTFE(Green)/NBR(Black)/Viton(Black)
<b>Window</b>	:Tempered Glass/Borosilicate Glass/Quartz Glass
<b>Connection Way</b>	:NPT,BSPP,BSPT Female Thread
<b>Max. Working Temperature</b>	:100°C / 212°F for Viton/NBR O-Ring and Plastic Balls 200°C / 392°F for PTFE O-Ring and Balls
<b>Max. Operating Pressure</b>	:1.6MPa / 16Bar / 232PSI(Up to 2.5MPa Customization)
<b>Compatible Medium</b>	:Water / Oil / Gas / Air / Liquids



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

## Wenzhou Luosimeng Machinery Co.,Ltd. (Sight Flow Indicator Manufacturer)