

## Carbon Steel Flow Indicator

<b>Product Type</b>	:SG-FQ11-26
<b>Product Sizes</b>	:DN32 to DN50(1 1/4”Inch to 2”Inch)
<b>Material of Construction</b>	
<b>Body&amp;Cap</b>	:SS304 / SS316 / SS316L,Carbon Steel
<b>Floating Ball</b>	:Plastic(Red/Blue)/PTFE(Red)
<b>Sealing Gaskets</b>	:PTFE(White)/NBR(Black)/Viton(Black)
<b>Window</b>	:Tempered Glass/Borosilicate Glass/Quartz Glass
<b>Connection Way</b>	:NPT,BSPP,BSPT Female Thread
<b>Max. Working Temperature</b>	:100°C / 212°F for Viton/NBR Gaskets and Plastic Balls 200°C / 392°F for PTFE Gaskets and Balls
<b>Max. Operating Pressure</b>	:1.6MPa / 16Bar / 232PSI(Up to 5.0MPa Customization)



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

**Wenzhou Luosimeng Machinery Co.,Ltd.**  
(Sight Flow Indicator Manufacturer)

Tel.:+86-577-86896383      Fax:+86-577-86998170      Mobile:+86-13091902237      Factory:102nd&201st Room,19th Building,No. 696,5th Binhai Road,Economic  
 Email:sales@roseoun.com.cn      sales1@roseoun.com.cn      roseounmachinery@hotmail.com      and Technological Developme Zone Wenzhou,Zhejiang P.R.China

Web:www.roseoun.com