

## PTFE Ball Flow Indicator

<b>Product Type</b>	:SG-FQ11-4
<b>Product Sizes</b>	:DN6 to DN25(1/8" Inch to 1" Inch)
<b>Material of Construction</b>	
<b>Body&amp;Cap</b>	:SS304 / SS316 / SS316L, Carbon Steel
<b>Floating Ball</b>	:Plastic(Red/Blue)/PTFE(Red)
<b>Sealing Gaskets</b>	:PTFE(White)/NBR(Black)/Viton(Black)
<b>Window</b>	:Tempered Glass/Borosilicate Glass/Quartz Glass
<b>Connection Way</b>	:NPT, BSPP, BSPT Female Thread
<b>Max. Working Temperature</b>	:100°C / 212°F for Viton/NBR Gaskets and Plastic Ball 200°C / 392°F for PTFE Gaskets and Balls
<b>Max. Operating Pressure</b>	:1.6MPa / 16Bar / 232PSI(Up to 5.0MPa Customization)
<b>Compatible Medium</b>	:Water / Oil / Gas / Air / Liquids



LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.



LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.



LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.



LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

**Wenzhou Luosimeng Machinery Co.,Ltd.**  
(Sight Flow Indicator Manufacturer)