

Polished Sight Flow Indicator

:SG-FO11-4 **Product Type**

Product Sizes :DN6 to DN25(1/8"Inch to 1"Inch)

Material of Construction

Body&Cap :SS304 / SS316 / SS316L, Carbon Steel

Floating Ball :Plastic(Red/Blue)/PTFE(Red)

:PTFE(White)/NBR(Black)/Viton(Black) **Sealing Gaskets**

Window :Tempered Glass/Borosilicate Glass/Quartz Glass

:NPT,BSPP,BSPT Female Thread **Connection Way**

Max. Working Temperature :100°C / 212°F for Viton/NBR Gaskets and Plastic Ball

200°C / 392°F for PTFE Gaskets and Ball

:1.6MPa / 16Bar / 232PSI(Up to 5.0MPa Customization) **Max. Operating Pressure**

Compatible Medium :Water / Oil / Gas / Air / Liquids





Wenzhou Luosimeng Machinery Co.,Ltd. (Sight Flow Indicator Manufacturer)

Tel.:+86-577-86896383 Fax:+86-577-86998170

Mobile:+86-13091902237 Factory:102nd&201st Room,19th Building,No. 696,5th Binhai Road,Economic and Technological Developme Zone Wenzhou, Zhejiang P.R.China

Email:sales@rosemoun.com.cn sales1@rosemoun.com.cn rosemounmachinery@hotmail.com