

Butt Weld Sight Flow Indicator

Product Type	:SG-YL61-20
Product Sizes	:DN6 to DN65(1/8”Inch to 2 1/2”Inch)
Material of Construction	
Body&Cap	:SS304 / SS316 / SS316L or Carbon Steel(WCB)
Sealing Gasket	:PTFE(White)/NBR(Black)/Viton(Black)
Sight Glass	:Tempered/Borosilicate/Quartz/Aluminosilicate Glass
Impeller/Rotor	:Plastic (Red) or PTFE (Red or Blue)
Connection Way	:Butt Weld/Socket Weld
Max. Working Temperature	:100°C / 212°F for Plastic Impeller&NBR or Viton Gasket 200°C / 392°F for PTFE Impeller&Gasket
Max. Operating Pressure	:1.6MPa / 16Bar / 232PSI (Up to 5.0MPa Customization)
Compatible Medium	:Water / Oil / Gas / Air / Liquids



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

Wenzhou Luosimeng Machinery Co.,Ltd.
(Sight Flow Indicator Manufacturer)