

## Sanitary Sight Glass Flow Indicator

<b>Product Type</b>	:SG-YL11-052A
<b>Product Sizes</b>	:DN15 to DN50(1/2”Inch to 2”Inch)
<b>Material of Construction</b>	
<b>Body&amp;Cap</b>	:SS304 / SS316 / SS316L or Brass
<b>Sealing O-Ring</b>	:PTFE(White)/NBR(Black)/Viton(Black)
<b>Sight Glass</b>	:Tempered Glass/Quartz Glass
<b>Impeller/Rotor</b>	:Plastic(Red)/PTFE(Red)
<b>Connection Way</b>	:NPT,BSPP,BSPT Male Thread
<b>Max. Working Temperature</b>	:100°C / 212°F for Plastic Impeller&NBR or NBR O-Ring 200°C / 392°F for PTFE Impeller&O-Ring
<b>Max. Operating Pressure</b>	:0.6MPa / 6Bar / 87PSI(Up to 1.6MPa Customization)
<b>Compatible Medium</b>	:Water / Oil / Gas / Air / Liquids



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

## Wenzhou Luosimeng Machinery Co.,Ltd. (Sight Flow Indicator Manufacturer)