

Pin Wheel Flow Indicator

Product Type	:SG-YL41-206
Product Sizes	:DN65 to DN100(2 1/2" Inch to 4" Inch)
Material of Construction	
Body&Cap&Bolt	:SS304 / SS316 / SS316L or Carbon Steel(WCB)
Sealing Gasket	:PTFE(White)/NBR(Black)/Viton(Black)/Graphite(Black)
Sight Glass	:Tempered/Borosilicate/Quartz/Aluminosilicate Glass
Impeller/Rotor	:Plastic (Red) or PTFE (Red or Blue)
Connection Way	:ANSI 150LB/300LB,JIS 5K/10K,DIN,GB Flange
Max. Working Temperature	:100°C / 212°F for Plastic Impeller&NBR or Viton Gasket 200°C / 392°F for PTFE Impeller&Gasket
Max. Operating Pressure	:1.6MPa / 16Bar / 232PSI (Up to 5.0MPa Customization)
Compatible Medium	:Water / Oil / Gas / Air / Liquids



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

Wenzhou Luosimeng Machinery Co.,Ltd.
(Sight Flow Indicator Manufacturer)

Tel.:+86-577-86896383 Fax:+86-577-86998170 Mobile:+86-13091902237 Factory:102nd&201st Room,19th Building,No. 696,5th Binhai Road,Economic and Technological Developme Zone Wenzhou,Zhejiang P.R.China

Web:www.rosemoun.com