

## Carbon Steel Flapper Flow Indicator

<b>Product Type</b>	:SG-ZT11-29A
<b>Product Sizes</b>	:DN8 to DN65(1/4”Inch to 2 1/2”Inch)
<b>Material of Construction</b>	
<b>Body&amp;Cap&amp;Flap</b>	:SS304 / SS316 / SS316L or Carbon Steel(WCB)
<b>Sealing Gasket</b>	:PTFE(White)/NBR(Black)/Viton(Black)
<b>Window</b>	:Tempered/Borosilicate/Quartz/Aluminosilicate Glass
<b>Connection Way</b>	:NPT,BSPP,BSPT Male Thread
<b>Max. Working Temperature</b>	:100°C / 212°F for Plastic or NBR Gasket 200°C / 392°F for PTFE Gasket
<b>Max. Operating Pressure</b>	:1.6MPa /16Bar /232PSI (Up to 5.0MPa Customization)
<b>Compatible Medium</b>	:Water / Oil / Gas / Air / Liquids etc



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

**Wenzhou Luosimeng Machinery Co.,Ltd.**  
(Sight Flow Indicator Manufacturer)