

## Paint Coating Double Window Sight Glass

<b>Product Type</b>	:SG-ZT41-205P
<b>Product Sizes</b>	:DN80 to DN100(3”Inch to 4”Inch)
<b>Material of Construction</b>	
<b>Body&amp;Cap</b>	:SS304 / SS316 / SS316L or Carbon Steel(WCB)
<b>Sealing Gaskets</b>	:PTFE(White)/NBR(Black)/Viton(Black)/Graphite(Black)
<b>Sight Glass</b>	:Tempered/Borosilicate/Quartz/Aluminosilicate Glass
<b>Connection Way</b>	:ANSI 150LB/300LB,JIS 5K/10K,DIN,GB Flange
<b>Max. Working Temperature</b>	:100°C / 212°F for NBR or Viton Gasket 200°C / 392°F for PTFE Gasket 1000°C / 1832°F for Graphite Gasket
<b>Max. Operating Pressure</b>	:1.6MPa / 16Bar / 232PSI (Up to 5.0MPa Customization)
<b>Compatible Medium</b>	:Water / Oil / Gas / Air / Liquids



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

### **Wenzhou Luosimeng Machinery Co.,Ltd.** (Sight Flow Indicator Manufacturer)