

## Sight Glass Liquid Flow Indicator

**Product Type** :SG-ZT41-205D  
**Product Sizes** :DN80 & DN100(3”Inch & 4”Inch)  
**Material of Construction**  
    **Body&Cap&Bolt** :SS304 / SS316 / SS316L or Carbon Steel(WCB)  
    **Sealing Gasket** :PTFE(White)/NBR(Black)/Viton(Black)/Graphite(Black)  
    **Sight Glass** :Tempered/Borosilicate/Quartz/Aluminosilicate Glass  
**Connection Way** :ANSI 150LB/300LB,JIS 5K/10K,DIN,GB Flange  
**Max. Working Temperature** :100°C / 212°F for NBR or Viton Gasket  
    200°C / 392°F for PTFE Gasket  
    1000°C / 1832°F for Graphite Gasket  
**Max. Operating Pressure** :1.6MPa / 16Bar / 232PSI (Up to 2.5MPa Customization)  
**Compatible Medium** :Water / Oil / Gas / Air / Liquids



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.



Wenzhou Luosimeng Machinery Co.Ltd.

**Wenzhou Luosimeng Machinery Co.,Ltd.**  
(Sight Flow Indicator Manufacturer)